OWELD 4600 EP3F - 2500 EP

CARATTERISTICHE - CHARACTERISTICS

MODELLO - *MODEL*	4600 EP3F	2500 EP
Potenza Massima kW *Max kW*	4,5	2,5
Produzione di Gas: litri/ora *Efficiency Max Gas CFH*	1.200 42	500 17
Consumo Acqua Distillata: litri/ora *Distilled Water Consumption: cu in/hr*	0,55 33	0,25 17
Temperatura Fiamma *Flame Temperature (°C)*	3.650	3.650
Peso kg *Weight lbs*	155 340	110 240
Diametro Massimo Ugello mm *Maximum Nozzle Diameter*	2	1,5
Ingombro cm (L x P x H) *Dimentions cm (W x P x H)*	55x87x73	55x67x73

4600 EP3F

Modello di medio/piccole dimensioni a controllo automatico adatto per:

- produzione motori elettrici di medie dimensioni.
- riparazione motori elettrici.
- trasformatori.
- frigoriferi, condizionatori, scambiatori di calore.
- collettori solari.
- costruzione e riparazione lame con metallo duro.
- lampadari, statue coppe e trofei in ottone.
- accessori moda e fibie di grosse dimensioni.
- lavorazione vetro artistico.

2500 EP

Modello di piccole dimensioni a controllo automatico adatto per:

- lucidatura di grossi spessori di plexiglass,fino a 250 mm in una solo passaggio.
- produzione motori elettrici di piccole dimensioni.
- accessori moda e fibie.
- lavorazione oro.

4600 EP3F

Oxyhydrogen flame ideal for:

- *OEM (medium/small size).*
- *electric motor repair shops.*
- *small transformers.*
- *refrigeration, air conditioning and heat exchangers*
- *solar collectors.*
- *manufacturing and repair saw blades with hard metal.*
- *fashion accessories (large size buckles etc.).*
- *manufacturing of trophies, chandeliers, statues and other brass articles.*
- *glass works.*

2500 EP

Oxyhydrogen flame ideal for:

- *thick acrylic edges flame polishing.*
- *OEM (small size).*
- *fashion accessories.*
- *gold accessories.*